

C38R

High Performance Cone Crusher

The McCloskey C38R recirculating cone crusher combines the productivity of the 38" cone with the versatility of a full screening and recirculating system, allowing operators to produce a high quality crushed and screened final product with one machine.

The C38R distinguishes itself as an entry-level cone with full level features like an anti-spin system, load and material level monitoring, fully hydraulic push button CSS adjust and full hydraulic relief system. The 5' x 10' High Energy Screenbox allows greater control over the final product.

FEEDER
Heavy duty Hardox®-lined steel hopper with feed rate adjusted via control panel, remote control or fully automatic regulation with feedback from the cone.



CRUSHER
Built to be reliable in the toughest operating conditions, the cone on the C38R produces 10 mm (3/8") (Fine liner) to 146 mm (5 3/4") product.



RECIRC SCREEN
5' x 10' High Energy Screenbox has user-friendly wedge system for faster screen change.



METAL DETECTOR
When metal is detected, the feeder stops automatically to protect the cone.

RECIRCULATION
Allows operators to produce a crushed and screened final product with one machine.



| | |
|------------------|------------------------|
| Engine | 350 hp (261 kW) Diesel |
| Transport Height | 11' 2" (3.40 m) |
| Transport Length | 56' 8.7" (17.29 m) |
| Transport Width | 10' 1" (3.08 m) |
| Stockpile Height | 9' 9" (2.965 m) |
| Weight | 100,300 lb (45,495 kg) |